

# ARMADILLO TAPE

## PRODUCT INFORMATION GUIDE

<b>Part Number:</b>	ARM-Series
<b>Application(s):</b>	Armadillo tape is our high performance long-lasting floor and aisle marking tape product. The tape has an aggressive adhesive backing and a scrim built into the carrier. The top surface is a durable weather and wear resistant surface that offers long-wear, reflectivity and anti-slip propoerties. The tape has a removable poly liner that is removed to expose the adhesive prior to application. Product may be used for both indoor and outdoor applications. Surface must be clean, dry and room temperature for best bonding.
<b>Adhesive:</b>	Permanent Weather-Resistant Adhesive.
<b>Key Features:</b>	Durability, Weather-Resistant, Anti-Slip and Reflective.
<b>Total Thickness:</b>	1.50mm (0.060")
<b>Application Temp:</b>	50°F (10°C) to 104°F (40°C) Maintained at this temperature for 24 hours for best bond.
<b>Service Temp:</b>	0°F (-18°C) to 150°F(65°C)
<b>Shelf Life:</b>	One year, when stored at 73°F (23°C), 50% +/- 5% relative humidity.

Property:	Test Method:	Measurement:
Thickness	PSTC-33	1.50mm (0.060")
Reflectivity	GB/T 24717-2009	250 mcd.lx <sup>-1</sup> m <sup>-2</sup> (rating applies to white material)
Peel Adhesion	PSTC 101 Mod	60 oz/inch (17 N / 25mm) Adhesion To Steel



This data is based on typical results achieved. It is the sole responsibility of the buyer or user to ensure that the product is suitable for any proposed end use or application and to ensure proper cleaning of the substrate to which it will be applied. This data in no way constitutes a specification, nor should it be seen as a recommendation for use. We accept no liability for any loss, damage or injury resulting from the use of these products or data.

Sept 2012.